

Resistor 0.25W, 1%, wired

Reference: AM6463

EAN13: -

UPC: 85332900

Product attributes:

Resistance: 0 Ohm, 0R0, 0.5 Ohm, R50, 1 Ohm, 1R0, 1.2 Ohm, 1R2, 1.1 Ohm, 1R1, 1.3 Ohm, 1R3, 1.5 Ohm, 1R5, 1.6 Ohm, 1R6, 1.8 Ohm, 1R8, 2 Ohm, 2R0, 2.2 Ohm, 2R2, 2.4 Ohm, 2R4, 2.7 Ohm, 2R7, 3 Ohm, 3R0, 3.3 Ohm, 3R3, 3.6 Ohm, 3R6, 3.9 Ohm, 3R9, 4.3 Ohm, 4R3, 4.7 Ohm, 4R7, 5.1 Ohm, 5R1, 5.6 Ohm, 5R6, 6.2 Ohm, 6R2, 6.8 Ohm, 6R8, 7.5 Ohm, 7R5, 8.2 Ohm, 8R2, 9.1 Ohm, 9R1, 12 Ohm, 12R, 10 Ohm, 10R, 15 Ohm, 15R, 18 Ohm, 18R, 20 Ohm, 20R, 22 Ohm, 22R, 27 Ohm, 27R, 30 Ohm, 30R, 33 Ohm, 33R, 36 Ohm, 36R, 39 Ohm, 39R, 43 Ohm, 43R, 47 Ohm, 47R, 51 Ohm, 51R, 56 Ohm, 56R, 62 Ohm, 62R, 75 Ohm, 75R, 68 Ohm, 68R, 82 Ohm, 82R, 91 Ohm, 91R, 100 Ohm, 100R, 180 Ohm, 180R, 120 Ohm, 120R, 150 Ohm, 150R, 200 Ohm, 200R, 220 Ohm, 220R, 240 Ohm, 240R, 270 Ohm, 270R, 300 Ohm, 300R, 330 Ohm, 330R, 360 Ohm, 360R, 390 Ohm, 390R, 430 Ohm, 430R, 470 Ohm, 470R, 510 Ohm, 510R, 560 Ohm, 560R, 620 Ohm, 620R, 680 Ohm, 680R, 750 Ohm, 750R, 820 Ohm, 820R, 910 Ohm, 910R, 1 kOhm, 1K0, 1.2 kOhm, 1K2, 1.5 kOhm, 1K5, 1.8 kOhm, 1K8, 2 kOhm, 2K0, 2.2 kOhm, 2K2, 2.4 kOhm, 2K4, 2.7 kOhm, 2K7, 3 kOhm, 3K0, 3.6 kOhm, 3K6, 3.3 kOhm, 3K3, 3.9 kOhm, 3K9, 4.3 kOhm, 4K3, 4.7 kOhm, 4K7, 5.1 kOhm, 5K1, 5.6 kOhm, 5K6, 6.2 kOhm, 6K2, 6.8 kOhm, 6K8, 7.5 kOhm, 7K5, 8.2 kOhm, 8K2, 9.1 kOhm, 9K1, 10 kOhm, 10K, 15 kOhm, 15K, 12 kOhm, 12K, 18 kOhm, 18K, 20 kOhm, 20K, 22 kOhm, 22K, 24 kOhm, 24K, 27 kOhm, 27K, 30 kOhm, 30K, 33 kOhm, 33K, 36 kOhm, 36K, 39 kOhm, 39K, 43 kOhm, 43K, 47 kOhm, 47K, 51 kOhm, 51K, 56 kOhm, 56K, 62 kOhm, 62K, 68 kOhm, 68K, 75 kOhm, 75K, 82 kOhm, 82K, 91 kOhm, 91K, 120 kOhm, 120K, 100 kOhm, 100K, 150 kOhm, 150K, 180 kOhm, 180K, 200 kOhm, 200K, 220 kOhm, 220K, 240 kOhm, 240K, 270 kOhm, 270K, 330 kOhm, 330K, 300 kOhm, 300K, 360 kOhm, 360K, 390 kOhm, 390K, 430 kOhm, 430K, 470 kOhm, 470K, 560 kOhm, 560K, 620 kOhm, 620K, 510 kOhm, 510K, 680 kOhm, 680K, 750 kOhm, 750K, 820 kOhm, 820K, 910 kOhm, 910K, 1 mOhm, 1M0, 1.5 mOhm, 1M5, 2 mOhm, 2M0, 3 mOhm, 3M0, 1.3 kOhm, 1K3, 10 mOhm, 10M, 3.3 mOhm, 3M3, 2.7 mOhm, 2M7, 4.7 mOhm, 4M7



Product features:

Power P: 0.25W

Temperature coefficient: $\pm 50\text{ppm}/^\circ\text{C}$

Tolerance: 1%

Execution: Axial

Weight: 0.2g

Product description:

Metallized resistor, parameters can be found in the product specification.

$I \pm 0.5\text{mm}$ $d \pm 0.3\text{mm}$ and $\pm 3\text{mm}$ and $\pm 0.05\text{mm}$ max. voltage 0.25W (1/4W) 6.5mm 2.5mm 28 mm 0.6mm 250V

