

# Power supply 24V, 83.3A - 2000W, 1 channel

Reference: AM9958

EAN13: -

UPC: 85044090

## Product attributes:

## Product features:

Input voltage: 85-265V AC, 50/60 Hz

Output voltage: 24V DC

Output current: 83.3A

Output power: 1200W

Waterproof grade: IP20



## Product description:

This 2000 watt power supply is a high performance and reliable industrial power supply with the ability to regulate voltage and current. It is a switching power supply that uses modern technology to achieve high efficiency and reliability in supplying power to your industrial applications. The power supply provides an adjustable output voltage of 0-24V and a current of up to 83.3A, making it an ideal choice for applications with high power requirements.

Thanks to the possibility of voltage and current regulation, you can adapt the power supply exactly to your needs and thus ensure a safe and reliable power supply for your devices. The source is equipped with a single channel and is ideal for industrial applications such as industrial automation, manufacturing, telecommunications, healthcare and many others.

Designed to be reliable and resistant to high temperatures and shocks, this power supply is equipped with protection functions against overvoltage, overheating and short circuit. It is therefore a safe and reliable choice for powering your industrial applications.

PWM control and regulation to ensure stable and accurate output voltage. Built-in forced cooling with two fans. Built-in EMI filter. Overcurrent, overvoltage, short circuit and thermal protection.

- Support analog signal output voltage 0-5V (0-10V) (linear increase)
- Support analog signal output current control 0-5V (0-10V) (5% ~ 100%)
- Adjustable resistor support to control output voltage and voltage
- Support for remote ON/OFF switching device
- N+1 feature support

Input voltage: 85-277 V AC, 50/60 Hz.

Output voltage: 0-24 V DC, max. 83.3A

Overload protection

Overvoltage protection

Short circuit protection

Steel construction

Certificates: CCC / FCC / CE, ROHS

Working temperature: -30~50°C

Ambient humidity: 0~95%

For internal use only

Size: 280x180x65mm

